



Fuse-link, low voltage, 80 A, AC 500 V, NH00, gL/gG, IEC, dual indicator

**EL Number**  
**(Norway)**

**80NHG00B**  
**1664016**

Product name	Eaton Bussmann series low voltage NH Fuse
Part no.	0NH FUSE 80A 500V gG SIZE 00 DUAL IND
EAN	5027590490788
Product Length/Depth	79 millimetre
Product height	58 millimetre
Product width	30 millimetre
Product weight	200.333333 gram
Compliances	RoHS Compliant CE Marked
Certifications	IEC 60269-2 IEC 60269-1 DIN 43620
Product Tradename	None
Product Type	Low voltage NH fuse
Product Sub Type	None
Amperage Rating	80 A
Voltage rating	500 V
Voltage type	AC
Breaking capacity	120 kA
Class	Class gG/gL
Fuse size	NH02
Insulated metal gripping lugs (IMGL)	No
Suitable for	SD00-D Single pole NH Fuse base TD00-D Tripe pole NH Fuse base Microswitch 170H0236 EBH Size 00 to 4 Horizontal fuse switch-disconnectors

### Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])		
Fuse construction type according to IEC 60269		NH00
Voltage type		AC
Rated current	A	80
Rated voltage AC	V	500
Rated voltage DC	V	
Rated switching capacity	kA	120
Utilization category		gL/gG (cable protection/equipment protection)
Type of fuse status indicator		Combination fuse status indicator
Insulated metal gripping lugs (IMGL)		No
Power loss at rated current	W	