



Eaton 9PX 1500i RT2U

Part no.
Catalog No.

Eaton 9PX 1500i RT2U
9PX1500IRT2U

Technical data ETIM 7.0

| Data and telecommunication (EG000037) / UPS (EC000382) | | |
|---|-----|---------------------------|
| Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) (ecI@ss10.0.1-27-04-06-90 [BAB258012]) | | |
| Input voltage | V | 100 - 276 |
| Primary frequency | Hz | 40 - 70 |
| Number of phases primary | | 1 |
| Output voltage | V | 200 - 240 |
| Secondary frequency | Hz | 50 - 60 |
| Output effective power | W | 1500 |
| Output apparent power | VA | 1500 |
| Type of interface | | Other |
| Number of phases secondary | | 1 |
| SNMP | | No |
| Voltage type | | AC |
| Height | mm | 86.5 |
| Width | mm | 440 |
| Depth | mm | 450 |
| Transition time for full load | min | 5 |
| Weight | kg | 18.9 |
| Network-management | | No |
| USV- technology | | Online |
| Construction type | | 482.6 mm (19 inch) device |
| Max. voltage distortion output (linear load) | % | 3 |
| Output power factor | | 1 |
| Overall efficiency | % | 92.5 |
| Efficiency in eco-mode | % | 97.5 |
| Potential free switch contact | | Yes |
| Auto shut down function | | Yes |
| Input connection | | Fixed connection |
| Number of output connections C13 | | 8 |
| Number of output connections C19 | | 0 |
| Number of output connections with protective contact (SCHUKO) | | 0 |
| Number of output connections fixed connection | | 0 |