



Eaton 9PX 2200i RT2U Netpack

Part no.

Eaton 9PX 2200i RT2U Netpack

Catalog No.

9PX2200IRTN

Technical data ETIM 7.0

| Data and telecommunication (EG000037) / UPS (EC000382) | | |
|--|-----|---------------------------|
| Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) (ec@ss10.0.1-27-04-06-90 [BAB258012]) | | |
| Input voltage | V | 100 - 276 |
| Primary frequency | Hz | 40 - 70 |
| Number of phases primary | | 1 |
| Output voltage | V | 200 - 240 |
| Secondary frequency | Hz | 50 - 60 |
| Output effective power | W | 2200 |
| Output apparent power | VA | 2200 |
| Type of interface | | Other |
| Number of phases secondary | | 1 |
| SNMP | | Yes |
| Voltage type | | AC |
| Height | mm | 86.5 |
| Width | mm | 440 |
| Depth | mm | 605 |
| Transition time for full load | min | 3.5 |
| Weight | kg | 24.5 |
| Network-management | | Yes |
| USV- technology | | Online |
| Construction type | | 482.6 mm (19 inch) device |
| Max. voltage distortion output (linear load) | % | 2 |
| Output power factor | | 1 |
| Overall efficiency | % | 93.5 |
| Efficiency in eco-mode | % | 98 |
| Potential free switch contact | | Yes |
| Auto shut down function | | Yes |
| Input connection | | C20 |
| Number of output connections C13 | | 8 |
| Number of output connections C19 | | 2 |
| Number of output connections with protective contact (SCHUKO) | | 0 |
| Number of output connections fixed connection | | 0 |