



Eaton 9PX 8000i HotSwap

Part no.

Catalog No.

Eaton 9PX 8000i HotSwap

9PX8KIBP



Powering Business Worldwide™

### Delivery program

|               |  |     |
|---------------|--|-----|
| Product range |  | UPS |
|---------------|--|-----|

### Technical data ETIM 7.0

|   |     |                     |
|---|-----|---------------------|
| Data and telecommunication (EG000037) / UPS (EC000382)  |     |                     |
| Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified)<br>(ecl@ss10.0.1-27-04-06-90 [BAB258012]) |     |                     |
| Input voltage   | V   | 100 - 276           |
| Primary frequency   | Hz  | 40 - 70             |
| Number of phases primary  |     | 1                   |
| Output voltage  | V   | 200 - 250           |
| Secondary frequency   | Hz  | 50 - 60             |
| Output effective power  | W   | 7200                |
| Output apparent power   | VA  | 8000                |
| Type of interface   |     | Other               |
| Number of phases secondary  |     | 1                   |
| SNMP  |     | Yes                 |
| Voltage type  |     | AC                  |
| Height  | mm  | 440                 |
| Width   | mm  | 260                 |
| Depth   | mm  | 700                 |
| Transition time for full load   | min | 5                   |
| Weight  | kg  | 84                  |
| Network-management  |     | Yes                 |
| USV- technology   |     | Online              |
| Construction type   |     | Free standing model |
| Max. voltage distortion output (linear load)  | %   | 2                   |
| Output power factor   |     | 0.9                 |
| Overall efficiency  | %   | 95                  |
| Efficiency in eco-mode  | %   | 98                  |
| Potential free switch contact   |     | Yes                 |
| Auto shut down function   |     | Yes                 |
| Input connection  |     | Fixed connection    |
| Number of output connections C13  |     | 0                   |
| Number of output connections C19  |     | 4                   |
| Number of output connections with protective contact (SCHUKO)   |     | 0                   |
| Number of output connections fixed connection   |     | 1                   |