



Fuse-link, LV, AC 500 V, 10 x 38 mm, gL/gG, IEC

**EL Number
(Norway)** **C10G0.5
1600203**

Similar to illustration

Product name	Eaton Busmann series low voltage cylindrical fuse
Part no.	CYLINDRICAL FUSE 10 x 38 0-5A GG 500V AC
EAN	5027590493376
Product Length/Depth	38 millimetre
Product height	10 millimetre
Product width	10 millimetre
Product weight	7.7 gram
Compliances	RoHS Compliant CE Marked
Certifications	IEC 60269
Product Tradename	None
Product Type	Low voltage cylindrical fuse
Product Sub Type	None
Amperage Rating	0.5 A
Voltage rating	500 V
Voltage type	AC
Breaking capacity	120 kA
Utilization category	gL/gG (cable protection/equipment protection)
Suitable for	CHM Modular fuse holder

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015])		
Model		Ceramic fuse
Size		10x38 mm
Voltage type		AC
Rated current	A	0.5
Rated voltage	V	500
Utilization category		gL/gG (cable protection/equipment protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Other
Release characteristic		Other
Breaking capacity	kA	120
Power loss at rated current	W	1.43