



Fuse-link, LV, 10 A, AC 500 V, 10 x 38 mm, aM, IEC

EL Number
(Norway)

C10M10
1600213

| | |
|----------------------|--|
| Product name | Eaton Bussmann series low voltage cylindrical fuse |
| Part no. | CYLINDRICAL FUSE 10 x 38 10A AM 500V AC |
| EAN | 5027590493635 |
| Product Length/Depth | 38 millimetre |
| Product height | 10 millimetre |
| Product width | 10 millimetre |
| Product weight | 8.2 gram |
| Compliances | GoST-R RoHS Compliant CE Marked |
| Certifications | IEC 60269 |
| Product Tradename | None |
| Product Type | Low voltage cylindrical fuse |
| Product Sub Type | None |
| Amperage Rating | 10 A |
| Voltage rating | 500 V |
| Voltage type | AC |
| Breaking capacity | 120 kA |
| Utilization category | aM (switchgear protection) |
| Suitable for | CHM Modular fuse holder |

Technical data ETIM 8.0

| | | |
|---|----|----------------------------|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015]) | | |
| Model | | Ceramic fuse |
| Size | | 10x38 mm |
| Voltage type | | AC |
| Rated current | A | 10 |
| Rated voltage | V | 500 |
| Utilization category | | aM (switchgear protection) |
| Rated operating frequency | Hz | 45 - 62 |
| Type of fuse status indicator | | Other |
| Release characteristic | | Other |
| Breaking capacity | kA | 120 |
| Power loss at rated current | W | 0.55 |