



Fuse-link, LV, 1 A, AC 690 V, 14 x 51 mm, gL/gG, IEC

EL Number
(Norway)

C14G1
1600270

Similar to illustration

| | |
|----------------------|--|
| Product name | Eaton Bussmann series low voltage cylindrical fuse |
| Part no. | C14G1 |
| EAN | 5027590493772 |
| Product Length/Depth | 51 millimetre |
| Product height | 14.3 millimetre |
| Product width | 14.3 millimetre |
| Product weight | 20.3 gram |
| Compliances | GoST-R RoHS Compliant CE Marked |
| Certifications | IEC 60269 |
| Product Tradename | None |
| Product Type | Low voltage cylindrical fuse |
| Product Sub Type | None |
| Amperage Rating | 1 A |
| Voltage rating | 690 V |
| Voltage type | AC |
| Breaking capacity | 80 kA |
| Utilization category | gL/gG (cable protection/equipment protection) |
| Suitable for | CH14 Modular fuse holder |

Technical data ETIM 8.0

| | | |
|---|----|---|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015]) | | |
| Model | | Ceramic fuse |
| Size | | 14x51 mm |
| Voltage type | | AC |
| Rated current | A | 1 |
| Rated voltage | V | 690 |
| Utilization category | | gL/gG (cable protection/equipment protection) |
| Rated operating frequency | Hz | 45 - 62 |
| Type of fuse status indicator | | Other |
| Release characteristic | | Other |
| Breaking capacity | kA | 80 |
| Power loss at rated current | W | 3.9 |