



Fuse-link, LV, 12 A, AC 690 V, 14 x 51 mm, aM, IEC

**EL Number
(Norway)** **C14M12
1600245**

Similar to illustration

Product name	Eaton Bussmann series low voltage cylindrical fuse
Part no.	CYLINDRICAL FUSE 14 x 51 12A AM 690V AC
EAN	5027590494373
Product Length/Depth	51 millimetre
Product height	14.3 millimetre
Product width	14.3 millimetre
Product weight	20.3 gram
Compliances	CE Marked RoHS Compliant
Certifications	IEC 60269
Product Tradename	None
Product Type	Low voltage cylindrical fuse
Product Sub Type	None
Amperage Rating	12 A
Voltage rating	690 V
Voltage type	AC
Breaking capacity	80 kA
Utilization category	aM (switchgear protection)
Suitable for	CH14 Modular fuse holder

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015])		
Model		Ceramic fuse
Size		14x51 mm
Voltage type		AC
Rated current	A	12
Rated voltage	V	690
Utilization category		aM (switchgear protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Other
Release characteristic		Other
Breaking capacity	kA	80
Power loss at rated current	W	0.88