

Fuse-link, LV, 16 A, AC 500 V, 14 \times 51 mm, aM, IEC, with striker



C14M16S

Product name	Eaton Bussmann series low voltage cylindrical fuse
Part no.	C14M16S
EAN	5027590494762
Product Length/Depth	51 millimetre
Product height	14 millimetre
Product width	14 millimetre
Product weight	21.2 gram
Compliances	RoHS Compliant CE Marked
Certifications	IEC 60269
Product Tradename	None
Product Type	Low voltage cylindrical fuse
Product Sub Type	None
Amperage Rating	16 A
Voltage rating	500 V
Voltage type	AC
Breaking capacity	120 kA
Utilization category	aM (switchgear protection)
Suitable for	CH14 Modular fuse holder

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)					
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015])					
Model			Ceramic fuse		
Size			14x51 mm		
Voltage type			AC		
Rated current		Α	16		
Rated voltage		V	500		
Utilization category			aM (switchgear protection)		
Rated operating frequency		Hz	45 - 62		
Type of fuse status indicator			Top fuse status indicator		
Release characteristic			Other		
Breaking capacity		kA	120		
Power loss at rated current		W	1.16		