

C14M50S

Similar to illustration

| | | |
|----------------------|--|---|
| Product name | | Eaton Busmann series low voltage cylindrical fuse |
| Part no. | | C14M50S |
| EAN | | 5027590494977 |
| Product Length/Depth | | 51 millimetre |
| Product height | | 14 millimetre |
| Product width | | 14 millimetre |
| Product weight | | 20.2 gram |
| Compliances | | RoHS Compliant CE Marked |
| Certifications | | IEC 60269 |
| Product Tradename | | None |
| Product Type | | Low voltage cylindrical fuse |
| Product Sub Type | | None |
| Amperage Rating | | 50 A |
| Voltage rating | | 400 V |
| Voltage type | | AC |
| Breaking capacity | | 120 kA |
| Utilization category | | aM (switchgear protection) |
| Suitable for | | CH14 Modular fuse holder |

Technical data ETIM 8.0

| | | |
|---|----|----------------------------|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015]) | | |
| Model | | Ceramic fuse |
| Size | | 14x51 mm |
| Voltage type | | AC |
| Rated current | A | 50 |
| Rated voltage | V | 400 |
| Utilization category | | aM (switchgear protection) |
| Rated operating frequency | Hz | 45 - 62 |
| Type of fuse status indicator | | Top fuse status indicator |
| Release characteristic | | Other |
| Breaking capacity | kA | 120 |
| Power loss at rated current | W | 2.9 |