



Fuse-link, LV, 25 A, AC 690 V, 22 x 58 mm, gL/gG, IEC, with striker



C22G25S

| | | |
|----------------------|--|--|
| Product name | | Eaton Bussmann series low voltage cylindrical fuse |
| Part no. | | C22G25S |
| EAN | | 5027590495394 |
| Product Length/Depth | | 58 millimetre |
| Product height | | 22 millimetre |
| Product width | | 22 millimetre |
| Product weight | | 55.9 gram |
| Compliances | | RoHS Compliant CE Marked |
| Certifications | | IEC 60269 |
| Product Tradename | | None |
| Product Type | | Low voltage cylindrical fuse |
| Product Sub Type | | None |
| Amperage Rating | | 25 A |
| Voltage rating | | 690 V |
| Voltage type | | AC |
| Breaking capacity | | 80 kA |
| Utilization category | | gG (cable protection/equipment protection) |
| Suitable for | | CH22 Modular fuse holder |

Technical data ETIM 8.0

| | | |
|---|----|---|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015]) | | |
| Model | | Ceramic fuse |
| Size | | 22x58 mm |
| Voltage type | | AC |
| Rated current | A | 25 |
| Rated voltage | V | 690 |
| Utilization category | | gL/gG (cable protection/equipment protection) |
| Rated operating frequency | Hz | 45 - 62 |
| Type of fuse status indicator | | Top fuse status indicator |
| Release characteristic | | Other |
| Breaking capacity | kA | 80 |
| Power loss at rated current | W | 3.3 |