



Fuse-link, LV, 50 A, AC 690 V, 22 x 58 mm, gL/gG, IEC, with striker

**C22G50S**

Product name		Eaton Bussmann series low voltage cylindrical fuse
Part no.		C22G50S
EAN		5027590495509
Product Length/Depth		58 millimetre
Product height		22 millimetre
Product width		22 millimetre
Product weight		55.3 gram
Compliances		RoHS Compliant CE Marked
Certifications		IEC 60269
Product Tradename		None
Product Type		Low voltage cylindrical fuse
Product Sub Type		None
Amperage Rating		50 A
Voltage rating		690 V
Voltage type		AC
Breaking capacity		80 kA
Utilization category		gG (cable protection/equipment protection)
Suitable for		CH22 Modular fuse holder

**Technical data ETIM 8.0**

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015])		
Model		Ceramic fuse
Size		22x58 mm
Voltage type		AC
Rated current	A	50
Rated voltage	V	690
Utilization category		gL/gG (cable protection/equipment protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Top fuse status indicator
Release characteristic		Other
Breaking capacity	kA	80
Power loss at rated current	W	5.5