

**EL Number  
(Norway)**                      **C22M16  
1600227**

Similar to illustration

<b>General specifications</b>		
Product name		Eaton Bussmann series low voltage cylindrical fuse
Part no.		C22M16
EAN		5027590495714
Product Length/Depth		58 millimetre
Product height		22.2 millimetre
Product width		22.2 millimetre
Product weight		52.7 gram
Compliances		RoHS Compliant CE Marked GoST-R
Certifications		IEC 60269
Product Tradename		None
Product Type		Low voltage cylindrical fuse
Product Sub Type		None
<b>Electrical data</b>		
Amperage Rating		16 A
Voltage rating		690 V
Voltage type		AC
Breaking capacity		80 kA
Utilization category		aM (switchgear protection)
<b>Compatible fuse holder</b>		
Suitable for		CH22 Modular fuse holder

### Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss13-27-14-20-02 [AFZ797018])		
Model		Ceramic fuse
Size		22x58 mm
Voltage type		AC
Rated current	A	16
Rated voltage	V	690
Utilization category		aM (switchgear protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Other
Release characteristic		Other
Breaking capacity	kA	80
Power loss at rated current	W	1.21