



Fuse-link, LV, 63 A, AC 690 V, 22 x 58 mm, aM, IEC

**EL Number**  
**(Norway)**

**C22M63**  
**1600233**

|                      |  |
|----------------------|--|
| Product name         | Eaton Bussmann series low voltage cylindrical fuse |
| Part no.             | CYLINDRICAL FUSE 22 x 58 63A AM 690V AC            |
| EAN                  | 5027590495899                                      |
| Product Length/Depth | 58 millimetre                                      |
| Product height       | 22.2 millimetre                                    |
| Product width        | 22.2 millimetre                                    |
| Product weight       | 55 gram  |
| Compliances          | CE Marked<br>RoHS Compliant<br>GoST-R              |
| Certifications       | IEC 60269  |
| Product Tradename    | None   |
| Product Type         | Low voltage cylindrical fuse                       |
| Product Sub Type     | None   |
| Amperage Rating      | 63 A   |
| Voltage rating       | 690 V  |
| Voltage type         | AC   |
| Breaking capacity    | 80 kA  |
| Utilization category | aM (switchgear protection)                         |
| Suitable for         | CH22 Modular fuse holder                           |

### Technical data ETIM 8.0

|   |    |                            |
|---|----|----------------------------|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)   |    |                            |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015]) |    |                            |
| Model   |    | Ceramic fuse               |
| Size  |    | 22x58 mm                   |
| Voltage type  |    | AC                         |
| Rated current   | A  | 63                         |
| Rated voltage   | V  | 690                        |
| Utilization category  |    | aM (switchgear protection) |
| Rated operating frequency   | Hz | 45 - 62                    |
| Type of fuse status indicator   |    | Other                      |
| Release characteristic  |    | Other                      |
| Breaking capacity   | kA | 80                         |
| Power loss at rated current   | W  | 4.46                       |