



Fuse-link, low voltage, 100 A, AC 415 V, 80 kA, BS88/A4, 31 x 110 mm, gM, BS, motor-rated



Powering Business Worldwide™

Part no. **100M200 415V AC BS88 FUSE**
 Catalog No. **CEO100M200**

Delivery program

| | | | |
|------------------------------|---|----|---------------------------------|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | low voltage |
| Rated current | I | A | 100 |
| Motor current rating | I | A | 100M200 |
| Rated voltage | | | AC 415 V |
| Construction size | | | BS88/A4 |
| Size | | | 31 x 110 mm |
| Utilization category | | | gM |
| Description | | | motor-rated |
| Breaking Capacity | | kA | 80 |
| usable for size/applications | | | general industrial applications |
| Standard/Approval | | | BS |
| Shape | | | offset bolted tags |
| Material | | | Ceramic body |
| Standards/Regulations | | | BS88-2 IEC 60269-2 |
| Optional accessories | | | fuse-holder RS100 |

Technical data ETIM 7.0

| | | | |
|---|--|----|-------|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) | | | |
| Construction size | | | Other |
| Rated current | | A | 100 |
| Rated voltage | | V | 415 |
| Voltage type | | | AC |
| Rated switching capacity | | kA | 80 |
| Utilization category | | | Other |
| Type of fuse status indicator | | | None |
| Insulated metal gripping lugs (IMGL) | | | No |