



Fuse-holder, low voltage, 50 A, AC 690 V, 14 x 51 mm, 3P + neutral, IEC, with indicator

CH143DNIU

Product name	Eaton Bussmann series low voltage cylindrical fuse holder
Part no.	CH143DNIU
EAN	5027590328234
Product Length/Depth	76 millimetre
Product height	92 millimetre
Product width	106 millimetre
Product weight	526 gram
Compliances	RoHS Compliant CE Marked
Certifications	IEC 60269-2 EAC UL Listed File E14853 IEC 60269-1
Product Tradename	None
Product Type	Low voltage cylindrical fuse holder
Product Sub Type	None
Amperage Rating	50 A
Voltage rating at AC	690 V a.c. (IEC) and 700 V a.c. (UL)
Voltage rating at DC	750 V d.c. (IEC)
Mounting method	DIN rail 2 x M4 Panel mounting screws
Optical defect indication	Yes
Fitted with:	Neon indicator
Degree of protection	IP20
Built-in depth	51.5 mm
Lockable	Yes
Width in number of modular spacings	6
Application	Industrial and Commercial applications
Fuse size	14 x 51 mm
Fuse type	C14G C14M
Accessories	JV-L Multipole connector kit, CH14-CTP IP20 Protection accessory

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Holder for cylindrical fuse (EC002705)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Holder for cylindrical fuse (ecl@ss10.0.1-27-14-21-21 [ADI305007])		
Nominal voltage	V	690
Mounting method		DIN rail
For fuse size		14x51 mm
Number of poles		3
Concurrently switching neutral conductor		No
Lockable		Yes
With optical defect indication		Yes
Width in number of modular spacings		6
Built-in depth	mm	51.5

