Switch disconnector, low voltage, 160 A, AC 690 V, NH000, AC21B, 3P, IEC



EBH00003TS5L

| Product name | Eaton Bussmann series low voltage NH fuse base |
|----------------------|------------------------------------------------|
| Part no. | EBH00003TS5L |
| EAN | 5906739002856 |
| Product Length/Depth | 110 millimetre |
| Product height | 200 millimetre |
| Product width | 95 millimetre |
| Product weight | 619 gram |
| Compliances | CE |
| Certifications | IEC/EN 60947-1 IEC 60947-3 |
| Product Tradename | None |
| Product Type | Low voltage NH fuse base |
| Product Sub Type | None |
| | |
| Amperage Rating | 160 A |
| Voltage rating | 690 |
| | |
| Number of poles | Three-pole |
| Mounting method | DIN rail 60 mm busbar mounting |

Technical data ETIM 8.0

| Low-voltage industrial components (EG000017) / Fuse switch disconnector | (EC001040) |
|-------------------------------------------------------------------------|------------|
|-------------------------------------------------------------------------|------------|

| Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnector (ecl@ss10.0.1-27-37-14-01 [AKF058013]) | | | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|----|-------------|--|
| Version as main switch | | | No | |
| Version as safety switch | | | No | |
| Max. rated operation voltage Ue AC | \ | V | 690 | |
| Rated permanent current lu | , | A | 160 | |
| Rated operation power at AC-23, 400 V | ŀ | kW | 0.064 | |
| Conditioned rated short-circuit current Iq | ŀ | kA | 0.1 | |
| Rated short-time withstand current lcw | ŀ | kA | 100 | |
| Suitable for fuses | | | NH000 | |
| Number of poles | | | 3 | |
| With error protection | | | No | |
| Type of electrical connection of main circuit | | | Cable clamp | |
| Cable entry | | | Other | |
| Equipped with connectors | | | No | |
| Suitable for floor mounting | | | No | |
| Suitable for front mounting | | | Yes | |
| Suitable for busbar mounting | | | No | |
| Type of control element | | | Cover grip | |
| Position control element | | | Front side | |
| Motor drive optional | | | No | |
| Motor drive integrated | | | No | |
| Version as emergency stop installation | | | No | |
| Degree of protection (IP), front side | | | IP30 | |