

Switch disconnecter, low voltage, 160 A, AC 690 V, NH00, AC23B, 3P, IEC



Powering Business Worldwide™

**Part no.** **SIZE 00 HOR FSD - 60MM BUS:M8 SCREWS BTM**  
**EBH0013TBM8**

Product name	Eaton Bussmann series low voltage NH fuse base
Part no.	SIZE 00 HOR FSD - 60MM BUS:M8 SCREWS BTM
EAN	5906739013715
Product Length/Depth	210 millimetre
Product height	140 millimetre
Product width	110 millimetre
Product weight	999 gram
Compliances	CE
Certifications	IEC 60947-3 IEC/EN 60947-1
Product Tradename	None
Product Type	Low voltage NH fuse base
Product Sub Type	None
Amperage Rating	160 A
Voltage rating	690
Number of poles	Three-pole
Mounting method	DIN rail 60 mm busbar mounting

## Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter (ecl@ss10.0.1-27-37-14-01 [AKF058013])			
Version as main switch			No
Version as safety switch			No
Max. rated operation voltage Ue AC	V		690
Rated permanent current Iu	A		160
Rated operation power at AC-23, 400 V	kW		0.064
Conditioned rated short-circuit current Iq	kA		0.08
Rated short-time withstand current Icw	kA		80
Suitable for fuses			NH00
Number of poles			3
With error protection			No
Type of electrical connection of main circuit			Screw connection
Cable entry			Other
Equipped with connectors			No
Suitable for floor mounting			No
Suitable for front mounting			No
Suitable for busbar mounting			Yes
Type of control element			Cover grip
Position control element			Front side
Motor drive optional			No
Motor drive integrated			No
Version as emergency stop installation			No
Degree of protection (IP), front side			IP30