## DATASHEET - SIZE 3 HOR FSD,M/PLATE: M12 SCREWS+M/S



Switch disconnector, low voltage, 630 A, AC 690 V, NH3, IEC, mounting plate type, with microswitch



Part no. Catalog No. SIZE 3 HOR FSD,M/PLATE: M12 SCREWS+M/S EBH303TM2-F

## Similar to illustration

Delivery program			
Product range			Fuse accessory
Basic function			Switch disconnector
Field of application			low voltage
Rated current	I	А	630
Rated voltage			AC 690 V
Construction size			NH3
Description			mounting plate type with microswitch lug terminal screws
Standard/Approval			IEC

## **Technical data ETIM 7.0**

Low-voltage industrial components (EG000017) / Fuse switch disconnector (EC001040)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnector (ecl@ss10.0.1-27-37-14-01 [AKF058013])

Version as main switch		No
Version as safety switch		No
Max. rated operation voltage Ue AC	V	690
Rated permanent current lu	А	630
Rated operation power at AC-23, 400 V	kW	252
Conditioned rated short-circuit current Iq	kA	25
Rated short-time withstand current lcw	kA	25
Suitable for fuses		NH3
Number of poles		3
With error protection		No
Type of electrical connection of main circuit		Screw connection
Cable entry		Other
Equipped with connectors		Yes
Suitable for ground mounting		No
Suitable for front mounting 4-hole		Yes
Suitable for busbar mounting		No
Type of control element		Cover grip
Position control element		Front side
Motor drive optional		No
Motor drive integrated		No
Version as emergency stop installation		No
Degree of protection (IP), front side		IP30