Switch disconnector, low voltage, 630 A, AC 690 V, NH3, AC22B, 3P, IEC



EBH303TS8

Product name	Eaton Bussmann series low voltage NH fuse base
Part no.	EBH303TS8
EAN	5906739002047
Product Length/Depth	250 millimetre
Product height	324 millimetre
Product width	140 millimetre
Product weight	4633 gram
Compliances	CE
Certifications	IEC 60947-3 IEC/EN 60947-1
Product Tradename	None
Product Type	Low voltage NH fuse base
Product Sub Type	None
Amperage Rating	630 A
Voltage rating	690
Number of poles	Three-pole
Mounting method	Mounting plate

Technical data ETIM 8.0

Technical data ETIM 8.0					
Low-voltage industrial components (EG000017) / Fuse switch disconnector (EC001040)					
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnector (ecl@ss10.0.1-27-37-14-01 [AKF058013])					
Version as main switch			No		
Version as safety switch			No		
Max. rated operation voltage Ue AC	V		690		
Rated permanent current lu	Α		630		
Rated operation power at AC-23, 400 V	kW	٧	0.252		
Conditioned rated short-circuit current Iq	kA	١.	0.025		
Rated short-time withstand current lcw	kA	4	25		
Suitable for fuses			NH3		
Number of poles			3		
With error protection			No		
Type of electrical connection of main circuit			Cable clamp		
Cable entry			Other		
Equipped with connectors			No		
Suitable for floor mounting			No		
Suitable for front mounting			Yes		
Suitable for busbar mounting			No		
Type of control element			Cover grip		
Position control element			Front side		
Motor drive optional			No		
Motor drive integrated			No		
Version as emergency stop installation			No		
Degree of protection (IP), front side			IP30		