



Switch disconnecter, low voltage, 1250 A, AC 500 V, NH4a, AC22B, 3P, IEC



**EBH403TM2-12**

Product name		Eaton Bussmann series low voltage NH fuse base
Part no.		EBH403TM2-12
EAN		5027590409414
Product Length/Depth		140 millimetre
Product height		324 millimetre
Product width		250 millimetre
Product weight		12890 gram
Compliances		CE
Certifications		IEC 60947-3 IEC/EN 60947-1
Product Tradename		None
Product Type		Low voltage NH fuse base
Product Sub Type		None
Amperage Rating		1250 A
Voltage rating		690
Number of poles		Three-pole

**Technical data ETIM 8.0**

Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter (ecI@ss10.0.1-27-37-14-01 [AKF058013])		
Version as main switch		No
Version as safety switch		No
Max. rated operation voltage Ue AC	V	690
Rated permanent current Iu	A	1,250
Rated operation power at AC-23, 400 V	kW	0.5
Conditioned rated short-circuit current Iq	kA	0.05
Rated short-time withstand current Icw	kA	50
Suitable for fuses		NH4a
Number of poles		3
With error protection		No
Type of electrical connection of main circuit		Screw connection
Cable entry		Other
Equipped with connectors		No
Suitable for floor mounting		No
Suitable for front mounting		Yes
Suitable for busbar mounting		No
Type of control element		Cover grip
Position control element		Front side
Motor drive optional		No
Motor drive integrated		No
Version as emergency stop installation		No
Degree of protection (IP), front side		IP30