

EBV0033SV0

| | | |
|----------------------|--|--|
| Product name | | Eaton Bussmann series low voltage NH fuse base |
| Part no. | | EBV0033SV0 |
| EAN | | 5906739017225 |
| Product Length/Depth | | 135 millimetre |
| Product height | | 715 millimetre |
| Product width | | 55 millimetre |
| Product weight | | 2434 gram |
| Compliances | | CE |
| Certifications | | IEC 60947-3 IEC/EN 60947-1 |
| Product Tradename | | None |
| Product Type | | Low voltage NH fuse base |
| Product Sub Type | | None |
| Voltage rating | | 690 |
| Number of poles | | Three-pole |
| Mounting method | | Busbar |

Technical data ETIM 8.0

| | | |
|--|----|--------------------------|
| Low-voltage industrial components (EG000017) / In-line fuse base (EC001046) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse strip (ecl@ss10.0.1-27-37-14-02 [AKF059013]) | | |
| Model | | Fuse switch disconnecter |
| Double interrupting | | No |
| Rated permanent current I _u | A | 160 |
| Distance between rail centre, 40 mm | | No |
| Distance between rail centre, 50 mm | | No |
| Distance between rail centre, 60 mm | | No |
| Distance between rail centre, 100 mm | | No |
| Distance between rail centre, 185 mm | | Yes |
| Max. rated operation voltage U _e AC | V | 690 |
| Conditioned rated short-circuit current I _q | kA | 0.08 |
| Type of electrical connection of main circuit | | Other |
| Number of poles | | 3 |
| Construction size fuse insert | | NH00 |
| Release indication | | None |