



**Fuse-link, low voltage, 400 A, AC 550 V, 80 kA, BS88/B3, BS88/B4, 59 x 136 mm, gM, BS, motor-rated**



Powering Business Worldwide™

**Part no. 400M500 550V AC MOTOR RATED FUSE**  
**Catalog No. ED400M500**

Similar to illustration

## Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	400
Motor current rating	I	A	400M500
Rated voltage			AC 550 V
Construction size			BS88/B3 BS88/B4
Size			59 x 136 mm
Utilization category			gM
Description			motor-rated
Breaking Capacity		kA	80
usable for size/applications			general industrial applications
Standard/Approval			BS
Shape			centre-bolted tags
Standards/Regulations			BS88-2 IEC 60269-2

## Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	400
Rated voltage		V	550
Voltage type			AC
Rated switching capacity		kA	80
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No