

Catalog No. EL800USBIN

Delivery program

Product range		UPS
---------------	--	-----

Technical data ETIM 6.0

Data and telecommunication (EG000037) / UPS (EC000382)		
Electric engineering, automation, process control engineering / Power supply / No-break power supply (complete) / No-break power supply (complete, unspecified) (ecl@ss8.1-27-04-06-90 [BAB258009])		
Input voltage	V	184 - 264
Primary frequency	Hz	50 - 60
Number of phases primary		1
Output voltage	V	230 - 240
Secondary frequency	Hz	50 - 60
Output effective power	W	500
Output apparent power	VA	800
Type of interface		USB
Number of phases secondary		1
SNMP		No
Voltage type		AC
Height	mm	263
Width	mm	81
Transition time for full load	min	1.5
Depth	mm	235
Weight	kg	4.1
Network-management		No
USV- technology		Offline
Construction type		482.6 mm (19 inch) device
Max. voltage distortion output (linear load)	%	0
Output power factor		0.6
Overall efficiency	%	98
Efficiency in eco-mode	%	98
Potential free switch contact		No
Auto shut down function		Yes
Input connection		Protective contact (SCHUKO)
Number of output connections C13		0
Number of output connections C19		0
Number of output connections with protective contact (SCHUKO)		4
Number of output connections fixed connection		0