



Eaton Ellipse PRO 1200 IEC

Part no. Eaton Ellipse PRO 1200 IEC
Catalog No. ELP1200IEC

Delivery program

Product range			UPS
---------------	--	--	-----

Technical data ETIM 7.0

Data and telecommunication (EG000037) / UPS (EC000382)			
Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) (ec1@ss10.0.1-27-04-06-90 [BAB258012])			
Input voltage	V		165 - 285
Primary frequency	Hz		50 - 60
Number of phases primary			1
Output voltage	V		220 - 240
Secondary frequency	Hz		50 - 60
Output effective power	W		750
Output apparent power	VA		1200
Type of interface			USB
Number of phases secondary			1
SNMP			No
Voltage type			AC
Height	mm		275
Width	mm		82
Depth	mm		390
Transition time for full load	min		2
Weight	kg		9.9
Network-management			No
USV- technology			Line-interactive
Construction type			482.6 mm (19 inch) device
Max. voltage distortion output (linear load)	%		0
Output power factor			0.6
Overall efficiency	%		95
Efficiency in eco-mode	%		95
Potential free switch contact			No
Auto shut down function			Yes
Input connection			Protective contact (SCHUKO)
Number of output connections C13			8
Number of output connections C19			0
Number of output connections with protective contact (SCHUKO)			0
Number of output connections fixed connection			0