

Catalog No. EMOB22

### Delivery program

|                                   |  |  |   |
|-----------------------------------|--|--|---|
| Type                              |  |  | Rack PDU  |
| Input Connection                  |  |  | C20   |
| Cord Length                       |  |  | 3m  |
| Input Voltage                     |  |  | 200-240V  |
| Phase                             |  |  | Single-phase  |
| Frequency Rating                  |  |  | 50/60 Hz  |
| Ethernet Interface                |  |  | Yes   |
| Serial Interface                  |  |  | Yes   |
| Form Factor                       |  |  | 0U (Vertical)   |
| Outlet Control                    |  |  | No  |
| Operating Temperature             |  |  | 0° to 60°C (32° to 140°F)   |
| Outlets                           |  |  | 20XC13 : 4XC19  |
| Number of Outputs C13             |  |  | 20  |
| Number of Outputs C19             |  |  | 4   |
| Amperage Rating                   |  |  | 16A   |
| Mounting Direction                |  |  | Vertical  |
| ETIM Class                        |  |  | EC002762  |
| Fitted With:                      |  |  | Ampere Meter<br>Display<br>Mounting material  |
| Electrical Connection             |  |  | Connecting cord with plug   |
| Evaluation                        |  |  | At distance   |
| Mounting Dimension (metrical)     |  |  | 52  |
| Mounting Dimension (standardised) |  |  | Metric  |
| Switchable                        |  |  | No  |
| Over Voltage Category             |  |  | 2   |
| Wattage                           |  |  | 3.84 kW max   |
| Communication                     |  |  | HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS  |
| SNMP                              |  |  | Yes   |
| Mass Configuration                |  |  | Yes   |
| Package Contents                  |  |  | PDU<br>mounting accessories<br>network cable<br>configuration cable<br>splitter for daisy-chaining<br>Quickstart<br>Safety Instructions |
| Number of Outputs C20             |  |  | 0   |
| Num of Outputs PC (SCHUKO)        |  |  | 0   |
| Number of Outputs (Other)         |  |  | 0   |
| Number of Outlets with Earth Pin  |  |  | 24  |

|       |  |       |
|-------|--|-------|
| Color |  | Black |
|-------|--|-------|

## Technical data ETIM 7.0

|  |    |                           |
|--|----|---------------------------|
| Domestic switching devices (EG000013) / Power distribution unit (PDU) (EC002762)   |    |                           |
| Electric engineering, automation, process control engineering / Electrical installation, device / Low-voltage distribution system (mobile) / Low-voltage distribution systems (mobile, unspecified) (ec1@ss10.0.1-27-14-26-90 [AKN612013]) |    |                           |
| Mounting dimension (standardised)  |    | Metric                    |
| Mounting dimension   | mm |                           |
| Mounting direction   |    | Vertical                  |
| Electrical connection  |    | Connecting cord with plug |
| Type of electric connection  |    | C20                       |
| Cable length   | m  | 3                         |
| Number of socket outlets with protective contact   |    | 0                         |
| Number of socket outlets with earth pin  |    | 24                        |
| Number of C13 socket outlets   |    | 20                        |
| Number of C19 socket outlets   |    | 4                         |
| Number of C20 socket outlets   |    | 0                         |
| Number of UK BS1363 sockets  |    |                           |
| number of socket outlets swiss standard type 13  |    |                           |
| number of socket outlets swiss standard type 15  |    |                           |
| number of socket outlets swiss standard type 23  |    |                           |
| number of socket outlets swiss standard type 25  |    |                           |
| Number of other socket outlets   |    |                           |
| Number of height units   |    |                           |
| Length   | mm | 1,604                     |
| Width  | mm | 53                        |
| Height   | mm | 52                        |
| Depth  | mm | 1,604                     |
| Supply voltage   | V  |                           |
| Over voltage category  |    | 2                         |
| Mains filter   |    | No                        |
| Switchable   |    | No                        |
| SNMP   |    | Yes                       |
| With display   |    | Yes                       |
| Evaluation   |    | At distance               |
| With LED indication  |    | No                        |
| With fuse  |    | No                        |
| Ampere meter   |    | Yes                       |
| With temperature measurement   |    | No                        |
| With mounting material   |    | Yes                       |