

Panel PC

**Part no. XP-504-15-TERMINAL
EP-400138**

Product name	Eaton XP Panel PC
Part no.	XP-504-15-TERMINAL
EAN	7640130099944
Product Length/Depth	412.1 millimetre
Product height	261.1 millimetre
Product width	75 millimetre
Product weight	3.8 kilogram
Certifications	CE
Product Tradename	XP
Product Type	Panel PC
Product Sub Type	None
Globally Marketable	Yes
Features	Customer individual configuration
Fitted with:	Touch screen
Degree of protection	NEMA 12 IP65
Degree of protection (front side)	IP65
Mounting method	Front build in possible
Voltage type	DC
Operating temperature - min	0 °C
Operating temperature - max	45 °C
Supply voltage at AC, 50 Hz - min	0
Supply voltage at AC, 50 Hz - max	0
Supply voltage at DC - min	20
Supply voltage at DC - max	28
Display type	TFT
Screen size (diagonal)	15.6 in

Technical data ETIM 8.0

Programmable logic controllers PLC (EG000024) / Industrial PC (EC001413)		
Information, communication and media technology / Computer system for industrial use / Industrial PC / Industrial PC (built-in) (ecl@ss10.0.1-19-20-01-02 [ACM011012])		
Supply voltage AC 50 Hz	V	0 - 0
Supply voltage AC 60 Hz	V	0 - 0
Supply voltage DC	V	20 - 28
Voltage type of supply voltage		DC
Number of HW-interfaces industrial Ethernet		0
Number of interfaces PROFINET		0
Number of HW-interfaces RS-232		0
Number of HW-interfaces RS-422		0
Number of HW-interfaces RS-485		0
Number of HW-interfaces serial TTY		0
Number of HW-interfaces USB		0
Number of HW-interfaces parallel		0

Number of HW-interfaces Wireless			0
Number of HW-interfaces other			0
Supporting protocol for PROFIBUS			No
Supporting protocol for CAN			No
Supporting protocol for INTERBUS			No
Supporting protocol for ASI			No
Supporting protocol for KNX			No
Supporting protocol for Modbus			No
Supporting protocol for Data-Highway			No
Supporting protocol for DeviceNet			No
Supporting protocol for SUCONET			No
Supporting protocol for LON			No
Supporting protocol for PROFINET IO			No
Supporting protocol for PROFINET CBA			No
Supporting protocol for SERCOS			No
Supporting protocol for Foundation Fieldbus			No
Supporting protocol for EtherNet/IP			No
Supporting protocol for AS-Interface Safety at Work			No
Supporting protocol for DeviceNet Safety			No
Supporting protocol for INTERBUS-Safety			No
Supporting protocol for PROFIsafe			No
Supporting protocol for SafetyBUS p			No
Supporting protocol for other bus systems			No
Radio standard Bluetooth			No
Radio standard Wi-Fi 802.11			No
Radio standard GPRS			No
Radio standard GSM			No
Radio standard UMTS			No
IO link master			No
Suitable for operating system Windows 9x			No
Suitable for operating system Windows 2000			No
Suitable for operating system Windows XP			No
Suitable for operating system Windows ME			No
Suitable for operating system Windows CE			No
Suitable for operating system Linux			No
Suitable for operating system Windows Vista			No
Suitable for operating system Windows 2003 Server			No
Suitable for operating system Windows 7			No
Suitable for operating system Windows 8			No
Suitable for other operating system			No
Preinstalled operating system			None
Max. main memory		MB	0
Degree of protection (IP)			IP65
Degree of protection (NEMA)			12
Operating temperature		°C	0 - 45
Construction type housing			Other
With hard disc			No
Processor type			Other
Processor clock rate		GHz	0
With graphic card			No
With sound card			No
With optical drive			No
With floppy disc drive			No
Number of free AGP-slots			0
Number of free PCI-slots			0

With other storage media			No
Number of free ISA-slots			0
Number of free PCMCIA-slots			0
Number of other free slots			0
Rail mounting possible			No
Wall mounting/direct mounting			No
Front built-in possible			Yes
Rack-assembly possible			No
Number of storage media bays			0
Suitable for safety functions			No
Width		mm	75
Height		mm	261.1
Depth		mm	412.1
Memory capacity hard disc		TB	0