



Fuse-link, low voltage, 63 A, AC 415 V, 80 kA, BS88/F2, 18 x 68 mm, gL/gG, BS



Powering Business Worldwide™

Part no. **63AMP 415V AC INDUSTRIAL**  
 Catalog No. **ESD63**

### Delivery program

|                              |   |    |                                 |
|------------------------------|---|----|---------------------------------|
| Product range                |   |    | Fuse                            |
| Basic function               |   |    | Fuse-link                       |
| Field of application         |   |    | low voltage                     |
| Rated current                | I | A  | 63                              |
| Rated voltage                |   |    | AC 415 V                        |
| Construction size            |   |    | BS88/F2                         |
| Size                         |   |    | 18 x 68 mm                      |
| Utilization category         |   |    | gL/gG                           |
| Breaking Capacity            |   | kA | 80                              |
| usable for size/applications |   |    | general industrial applications |
| Standard/Approval            |   |    | BS                              |
| Shape                        |   |    | offset bladed tags              |
| Standards/Regulations        |   |    | BS88-2<br>IEC 60269-2           |
| Optional accessories         |   |    | fuse-holder 63ENS and SC63      |

### Technical data ETIM 7.0

|   |  |    |   |
|---|--|----|---|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)   |  |    |   |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) |  |    |   |
| Construction size   |  |    | Other   |
| Rated current   |  | A  | 63  |
| Rated voltage   |  | V  | 415   |
| Voltage type  |  |    | AC  |
| Rated switching capacity  |  | kA | 80  |
| Utilization category  |  |    | gL/gG (cable protection/equipment protection) |
| Type of fuse status indicator   |  |    | None  |
| Insulated metal gripping lugs (IMGL)  |  |    | No  |