



Part no.  
Article no.

FUSETRON DUAL-ELEMENT CLASS RK5  
FRN-R-12

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	12
Rated voltage			AC 250 V
Size			14 x 51 mm
Utilization category			RK5
Description			dual-element
usable for size/applications			motor overload protection ground fault protection short-circuit protection
Release characteristic	class		time-delay
Standard/Approval			UL
Standards/Regulations			CE UL Listed, Standard 248-12 Class RK-5, Guide JDDZ, File E4273 CSA Certified, C22.2 No. 248.12, Class 1422-02, File 53787
Time delay			time-delay 8 seconds (minimum) at 500% of rated current

### Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			Other
Nominal rated current		A	12
Nominal rated voltage		V	250
Utilization category			Other
Type of fuse status indicator			None

### Additional product information (links)

Product datasheet (PDF)	<a href="http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1019_FRN-R_1_10-60A.pdf">http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1019_FRN-R_1_10-60A.pdf</a>
-------------------------	---