Fuse-link, low voltage, AC 415 V, BS88/F2, 18 x 59 mm, gM, BS



NSD32M50

Similar to illustration

Product name Part no.	Eaton Bussmann series low voltage British standard fuse
Part no.	Euton Bussiliani sonos ion Voltago British standara raso
	NSD32M50
EAN	5027590504911
Product Length/Depth	59 millimetre
Product height	18 millimetre
Product width	18 millimetre
Product weight Product weight	26.8 gram
Compliances	RoHS Compliant
Product Tradename	None
Product Type	Low voltage British standard fuse
Product Sub Type	None
lectrical data	
Amperage Rating	50 A
Voltage rating	415 V
Voltage type	AC
Breaking capacity	80 kA
Class	Class gM
Product specifications	
Application	general industrial applications
Fuse type	NSD
Fuse size	BS88/F1
Fitted with:	Offset bladed tags
Connection	Blade end
Compatible fuse holder	
Suitable for	32NNS Safeloc fuse holder SC32 Safeclip fuse holder

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)					
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])					
Fuse system according to IEC 60269			Fuse system E		
Fuse construction type according to IEC 60269			F2		
Type of current			AC		
Rated voltage AC	V	V	415		
Rated voltage DC	٧	V			
Rated current	A	A	50		
Utilization category			gM (motor protection)		
Breaking capacity	k	kA	80		
Colour code			None		
Type of fuse status indicator			None		
Power loss at rated current	V	W	1.4		
Mounting holes					
Centre-to-centre distance of connections	n	mm			