



Eaton PDU3XMV6G20

Eaton Tripp Lite series metered outlet PDU, 3PH, 0U, IEC-60309 input, 6 ft cord, 11.5kW, 16A, 360-415V, 45 Outlets (36) C13 (9) C19, TAA

Allgemeine Spezifikation

PRODUCT NAME	Eaton Tripp Lite series local metered rack PDU
CATALOG NUMBER	PDU3XMV6G20
PRODUCT LENGTH/DEPTH	1.93 in
PRODUCT HEIGHT	70 in
PRODUCT WIDTH	2.2 in
PRODUCT WEIGHT	9 lb
COMPLIANCES	RoHS FCC Class A CE Marked TAA Compliant
CERTIFICATIONS	RETIE IEC 62368-1 UL 62368-1 NOM
UPC	037332163912

Produktspezifikationen

Downloads

FORM FACTOR	0U (Vertical)
PACKAGE CONTENTS	<ul style="list-style-type: none">• Local Metered rackmount PDU with pre-installed mounting buttons• Cord retention brackets• Spare installation buttons (2 9mm / 4 6mm)• Rack mounting brackets• Owner's manual
OPERATING TEMPERATURE	32° to 104°F (0° to 40°C)
MOUNTING DIRECTION	Vertical
MATERIAL	Metal
INPUT CONNECTION	309-520P6
CORD LENGTH	6 ft
AMPERAGE RATING	16A
ELECTRIC CURRENT - MAX	16
PHASE	Three-phase
FREQUENCY RATING	50/60 Hz
NUMBER OF OUTPUTS C13	36
NUMBER OF OUTPUTS C19	9
FEATURES	Flex Center
FRONT PANEL LCD DISPLAY	Set of 3 digital meters report per-phase output current in amps (L1, L2, L3)
OUTPUT RECEPTACLES	C13 C19
RECOMMENDED ELECTRICAL SERVICE	Three-phase 16A 360-415V service
REPORTED LOAD SEGMENTS	Supports local monitoring of current for each output phase (16A balanced max per output load banks L1, L2 and L3); Outlets are color-coded and labeled for easy phase and load bank identification; L1-N feeds black outlets; L2-N feeds dark-gray outlets; L3-N feeds light-gray outlets
OUTPUT RECEPTACLES	Compatible with Eaton

DETAILS	Tripp Lite Power Cords
RECEPTACLES	<ul style="list-style-type: none"> • C13 • C19
INPUT CORD LENGTH	6 ft
TAA COMPLIANCE	Yes
PRODUCT FEATURES	TAA Compliant
AMPERAGE RATING DETAILS	Agency de-rated to 16A continuous
OPERATING ELEVATION	0-10000 ft. (0-3000 m)
OPERATING TEMPERATURE RANGE	32° to 104°F (0° to 40°C)
OUTPUT NOMINAL VOLTAGE	208-240V
RELATIVE HUMIDITY	5% to 95% non-condensing
FORM FACTORS SUPPORTED	Vertical rackmount installation supported with included mounting brackets; supports toolless mounting in button-mount compatible racks
OUTPUT CAPACITY DETAILS	11.5kW (415/240V), 11.1kW (400/230V), 10.5kW (380/220V), 10kW (360/208V) total capacity; 16A max per output phase (L1-L2, L2-L3, L3-L1); 16A max per C19 outlet; 12A max (10A CE) per C13 outlet
OUTPUT CAPACITY (KW)	11.5
STORAGE TEMPERATURE	-22° to 122°F (-30° to 50°C)
PRODUCT HIGHLIGHTS	<p>36 C13 and 9 C19 single phase outlets; Included cord retention brackets IEC-309 Red 16/20A (3P+N+E) 3 phase input; 6ft 1.8m line cord 70in / 1778mm 0U vertical format, toolless button-mount installation</p> <p>Set of 3 digital meters reports output load level per phase in amps</p> <p>Compatible with Eaton Tripp Lite power cords to simplify deployment and enhance reliability</p> <p>Local metered 11.5kW 3 Phase 360-415V input / 208-240V output PDU</p>
PDU PLUG TYPE	520P6

PDU TYPE	Local metered
PDU INPUT VOLTAGE	360 240 415
PDU FORM FACTOR	Vertical (0U)
TOTAL OUTLETS	45

PROJEKTNAME:

PROJEKTNUMMER:

ERSTELLT VON:

DATUM:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Irland
Eaton.com

© 2026 Eaton. Alle Rechte vorbehalten.

Folgen Sie uns in den sozialen Netzwerken und erhalten Sie aktuelle Produkt- und Supportinformationen.

