

## Eaton PDUMH16HV



Eaton Tripp Lite series metered outlet PDU, 1PH, 1U, IEC-60309, 8 ft cord, 3.7kW, 16A, 208/230V, 10 Outlets (8) C13 (2) C19 TAA



### Allgemeine Spezifikation

<b>PRODUCT NAME</b>	Eaton Tripp Lite series metered outlet PDU
<b>CATALOG NUMBER</b>	PDUMH16HV
<b>PRODUCT LENGTH/DEPTH</b>	6.5 in
<b>PRODUCT HEIGHT</b>	1.75 in
<b>PRODUCT WIDTH</b>	17.5 in
<b>PRODUCT WEIGHT</b>	3.9 lb
<b>COMPLIANCES</b>	RoHS CE Marked FCC Class A EAC TAA Compliant
<b>CERTIFICATIONS</b>	RETIE GoST-R NOM IEC 62368-1
<b>UPC</b>	037332182791

## Produktspezifikationen

<b>FORM FACTOR</b>	1U
<b>PACKAGE CONTENTS</b>	<ul style="list-style-type: none"><li>• Rackmount PDU</li><li>• Rack mounting brackets</li><li>• Plug lock inserts</li><li>• IEC-309 Blue 16A input cord</li></ul>
<b>OPERATING TEMPERATURE</b>	32° to 104°F (0° to 40°C)
<b>MOUNTING DIRECTION</b>	Horizontal
<b>MATERIAL</b>	Metal
<b>INPUT CONNECTION</b>	IEC-60309 16A BLUE (2P+E)
<b>CORD LENGTH</b>	8.2 ft
<b>AMPERAGE RATING</b>	16A
<b>ELECTRIC CURRENT - MAX</b>	16
<b>PHASE</b>	Single-phase
<b>FREQUENCY RATING</b>	50/60 Hz
<b>NUMBER OF OUTPUTS C13</b>	8
<b>NUMBER OF OUTPUTS C19</b>	2
<b>FEATURES</b>	Flex Center
<b>FRONT PANEL LCD DISPLAY</b>	Digital display reports total PDU output current in amps
<b>OUTPUT RECEPTACLES</b>	C13 C19
<b>GROUNDING OPTIONS</b>	Front panel grounding lug
<b>MINIMUM REQUIRED RACK DEPTH</b>	10 in
<b>RECOMMENDED ELECTRICAL SERVICE</b>	Single-phase 16/20A 230/208V service
<b>RECEPTACLES</b>	<ul style="list-style-type: none"><li>• C13</li><li>• C19</li></ul>
<b>INPUT CORD LENGTH</b>	8.2 ft
<b>PRODUCT FEATURES</b>	TAA Compliant
<b>OPERATING ELEVATION</b>	0-10000 ft. (0-3000 m)
<b>OPERATING TEMPERATURE RANGE</b>	32° to 104°F (0° to 40°C)
<b>OUTPUT NOMINAL VOLTAGE</b>	208/230V
<b>RELATIVE HUMIDITY</b>	5% to 95% non-

## Downloads

	condensing
<b>FORM FACTORS SUPPORTED</b>	1U rackmount. Includes mounting accessories for 2-4 post racks
<b>OUTPUT CAPACITY DETAILS</b>	3.7kW (230V), 3.3kW (208V) / 16A total capacity; 16A max per C19 outlet; 12A (10A CE) max per C13 outlet
<b>STORAGE TEMPERATURE</b>	-22° to 122°F (-30° to 50°C)
<b>PRODUCT HIGHLIGHTS</b>	1U horizontal rackmount; digital current meter Local metered single phase 16A 208/230V PDU TAA Compliant C20 input with IEC-309 Blue 16A input; 2.5m line cord 10 total outlets (8 C13, 2 C19); 6.5 in. / 16.5 cm depth
<b>PDU PLUG TYPE</b>	IEC-60309 16A BLUE (2P+E)
<b>PDU TYPE</b>	Local metered
<b>PDU INPUT VOLTAGE</b>	208
<b>PDU FORM FACTOR</b>	Horizontal (1U)

---

**PROJEKTNAME:**

**PROJEKTNUMMER:**

**ERSTELLT VON:**

**DATUM:**

---



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Irland  
Eaton.com

Folgen Sie uns in den sozialen Netzwerken und erhalten Sie aktuelle Produkt- und Supportinformationen.



© 2026 Eaton. Alle Rechte vorbehalten.