

Eaton PDUMV20HV



Eaton Tripp Lite series metered outlet PDU, 1PH, 0U, C20/L6-20P input, 10 ft cord, 3.7kW, 16A, 208/230V, 38 Outlets (32) C13 (6) C19



Allgemeine Spezifikation

PRODUCT NAME	Eaton Tripp Lite series local metered rack PDU
CATALOG NUMBER	PDUMV20HV
PRODUCT LENGTH/DEPTH	63.75 in
PRODUCT HEIGHT	3.75 in
PRODUCT WIDTH	2.25 in
PRODUCT WEIGHT	5.2 lb
COMPLIANCES	EAC CE Marked RoHS TAA Compliant
CERTIFICATIONS	NOM GoST-R RETIE IEC 62368-1
UPC	037332139344

Produktspezifikationen

Downloads

FORM FACTOR	0U (Vertical)
PACKAGE CONTENTS	<ul style="list-style-type: none"> • PDUMV20HV 63.75 inch basic PDU • Plug-lock inserts (6 C20, 32 C13) • Spare installation buttons, 2.9 mm/4.6 mm • 10-ft. (3.05 m) detachable C19-to-L620P input cordset • Mounting hardware • Owner's Manual
OPERATING TEMPERATURE	32° to 104°F (0° to 40°C)
MOUNTING DIRECTION	Vertical
MATERIAL	Aluminum
INPUT CONNECTION	L6-20P
CORD LENGTH	10 ft
AMPERAGE RATING	16A
ELECTRIC CURRENT - MAX	16
PHASE	Single-phase
FREQUENCY RATING	50/60 Hz
NUMBER OF OUTPUTS C13	32
NUMBER OF OUTPUTS C19	6
FEATURES	Flex Center
FRONT PANEL LCD DISPLAY	Digital meter reports PDU output current in amps
OUTPUT RECEPTACLES	C13 C19
RECOMMENDED ELECTRICAL SERVICE	Single-phase 16/20A 230/208V service
OUTPUT RECEPTACLES DETAILS	Compatible with Eaton Tripp Lite Power Cords
RECEPTACLES	<ul style="list-style-type: none"> • C13 • C19
INPUT CORD LENGTH	10 ft
TAA COMPLIANCE	No
PRODUCT FEATURES	L6-20P detachable cordset, C20 inlet available
AMPERAGE RATING	Agency de-rated to 16A

DETAILS	continuous
OPERATING ELEVATION	0-10000 ft. (0-3000 m)
OPERATING TEMPERATURE RANGE	32° to 104°F (0° to 40°C)
OUTPUT NOMINAL VOLTAGE	208/230V
RELATIVE HUMIDITY	0-95% non-condensing
FORM FACTORS SUPPORTED	0u vertical installation in equipment racks, plus under-counter and wallmount
OUTPUT CAPACITY DETAILS	3.68kW (230V), 3.33kW (208V) / 16A total capacity; 16A max per C19 outlet; 12A (10A CE) max per C13 outlet
OUTPUT CAPACITY (KW)	3.7
STORAGE TEMPERATURE	-22° to 122°F (-30° to 50°C)
PRODUCT HIGHLIGHTS	<p>Ready for immediate toolless 0U installation</p> <p>C20 inlet accepts a variety of 16A international cordsets</p> <p>10ft / 3m detachable input cable with NEMA L6-20P plug</p> <p>38 output receptacles (6 C19, 32 C13); Compatible with Eaton Tripp Lite power cords</p> <p>Local metered single phase 16A 208/230V 0U</p> <p>63.75in / 162cm vertical rackmount PDU</p> <p>Two-digit meter reports output current in amps</p>
PDU PLUG TYPE	L6-20P
PDU TYPE	Local metered
PDU INPUT VOLTAGE	208
PDU FORM FACTOR	Vertical (0U)
TOTAL OUTLETS	38

PROJEKTNAME:

PROJEKTNUMMER:

ERSTELLT VON:

DATUM:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Irland
Eaton.com

© 2026 Eaton. Alle Rechte vorbehalten.

Folgen Sie uns in den sozialen
Netzwerken und erhalten Sie aktuelle
Produkt- und Supportinformationen.

