



Fuse-link, high speed, 160 A, DC 1500 V, 1XL, 51 x 189 mm, gPV, IEC, UL, with indicator, bolted



Part no. FU5E 160A 1500V 1XL PV BOLT-IN VER
Catalog No. PV-160A-1XL-B-15

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	160
Rated voltage			DC 1500 V
Construction size			1XL
Size			51 x 189 mm
Utilization category			gPV
Status indicator			with indicator
Breaking Capacity		kA	30
usable for size/applications			photovoltaic array combiners and disconnects
Standard/Approval			UL IEC
Shape			square body with bolted blades
Standards/Regulations			IEC 60269-6 UL 2579

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	160
Rated voltage		V	1500
Voltage type			DC
Rated switching capacity		kA	30
Utilization category			gPV (photovoltaic protection)
Type of fuse status indicator			Centre fuse status indicator
Insulated metal gripping lugs (IMGL)			No