## Fuse-link, low voltage, 25 A, AC 415 V, BS88, 13 x 29 mm, gL/gG, BS $\,$



## SMD25

General specifications	
Product name	Eaton Bussmann series low voltage British standard fuse
Part no.	SMD25
EAN	5027590511025
Product Length/Depth	29 millimetre
Product height	16 millimetre
Product width	16 millimetre
Product weight	11.75 gram
Compliances	RoHS Compliant CE Marked
Certifications	EAC IEC 60269 BS88
Product Tradename	None
Product Type	Low voltage British standard fuse
Product Sub Type	None
Electrical data	
Amperage Rating	25 A
Voltage rating	415 V
Voltage type	AC
Breaking capacity	80 kA
Class	Class gG/gL
Product specifications	
Application	street lighting cut-outs
Fuse type	SMD
Connection	Ferrule end x ferrule end

## **Technical data ETIM 9.0**

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)				
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss13-27-14-20-02 [AFZ797018])				
Model			Ceramic fuse	
Size			13x29 mm	
Voltage type			AC	
Rated current		Α	25	
Rated voltage		V		
Utilization category			gG (cable protection/equipment protection)	
Rated operating frequency		Hz	45 - 62	
Type of fuse status indicator			Other	
Release characteristic			Other	
Breaking capacity		kA	80	
Power loss at rated current		W	2.2	