## Fuse-link, LV, 6 A, AC 415 V, BS88, $13 \times 29$ mm, gL/gG, BS



## SMD6

General specifications	
Product name	Eaton Bussmann series low voltage British standard fuse
Part no.	SMD6
EAN	5027590511056
Product Length/Depth	29 millimetre
Product height	16 millimetre
Product width	16 millimetre
Product weight	10.2 gram
Compliances	CE Marked RoHS Compliant
Certifications	EAC IEC 60269 BS88
Product Tradename	None
Product Type	Low voltage British standard fuse
Product Sub Type	None
Electrical data	
Amperage Rating	6 A
Voltage rating	415 V
Voltage type	AC
Breaking capacity	80 kA
Class	Class gG/gL
Product specifications	
Application	street lighting cut-outs
Fuse type	SMD
Connection	Ferrule end x ferrule end

## **Technical data ETIM 9.0**

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)				
Electric engineering, automation, process control engineering / Electrical insta	llation, device / Sa	fety fuse i	nserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])	
Fuse system according to IEC 60269			Other	
Fuse construction type according to IEC 60269			Other	
Type of current			AC	
Rated voltage AC		V	415	
Rated voltage DC		V		
Rated current		Α	6	
Utilization category			gG (cable protection/equipment protection)	
Breaking capacity		kA	80	
Colour code			None	
Type of fuse status indicator			None	
Power loss at rated current		W	1.9	
Mounting holes				
Centre-to-centre distance of connections		mm		