Fuse-link, high speed, 32 A, AC 1200 V, DC 660 V, BS2692-1, 22 x 139 mm, BS  $\,$ 



## TAC32

| Product name         | Eaton Bussmann series high speed traction fuse |
|----------------------|--|
| Part no.             | TAC32  |
| EAN                  | 5027590512855                                  |
| Product Length/Depth | 139 millimetre                                 |
| Product height       | 23 millimetre                                  |
| Product width        | 23 millimetre                                  |
| Product weight       | 102.6 gram                                     |
| Compliances          | Not Applicable                                 |
| Certifications       | BS 2692-1                                      |
| Product Tradename    | None   |
| Product Type         | High speed traction fuse                       |
| Product Sub Type     | None   |
|                      |  |
| Amperage Rating      | 32 A   |
| Voltage rating       | 1200 V   |
| Interrupt rating     | 63 KAIC  |
|                      |  |
| Application          | traction                                       |
| Fuse indicator       | None   |

## **Technical data ETIM 8.0**

| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)                |                           |             |   |
|--|---------------------------|-------------|---|
| Electric engineering, automation, process control engineering / Electrical | installation, device / Sa | fety fuse i | nserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011]) |
| Fuse construction type according to IEC 60269                              |                           |             | Other   |
| Type of current  |                           |             | AC/DC   |
| Rated voltage AC   |                           | V           | 1,200   |
| Rated voltage DC   |                           | V           | 660   |
| Rated current  |                           | Α           | 32  |
| Utilization category   |                           |             | Other   |
| Breaking capacity  |                           | kA          | 63  |
| Colour code  |                           |             | None  |
| Type of fuse status indicator  |                           |             | None  |
| Power loss at rated current  |                           | W           |   |
| Mounting holes   |                           |             | M5  |
| Centre-to-centre distance of connections                                   |                           | mm          | 124   |