Fuse-link, low voltage, 16 A, AC 660 V, DC 460 V, BS88, 27 x 112 mm, gL/gG, RS



## **TB16**

Product name	Eaton Bussmann series low voltage British standard fuse
Part no.	TB16
EAN	5027590512930
Product Length/Depth	112 millimetre
Product height	27 millimetre
Product width	27 millimetre
Product weight	86.2 gram
Compliances	CE Marked RoHS Compliant
Certifications	IEC 60269 BS88 EAC
Product Tradename	None
Product Type	Low voltage British standard fuse
Product Sub Type	None
Amperage Rating	16 A
Voltage rating	660 V
Voltage type	AC/DC
Breaking capacity	80 kA
Class	Class gG/gL
Application	general industrial applications
Fuse type	ТВ
Fitted with:	Centre bolted tags
Connection	97 mm fixing centre

## **Technical data ETIM 8.0**

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)					
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])					
Fuse construction type according to IEC 60269			Other		
Type of current			AC/DC		
Rated voltage AC		٧	660		
Rated voltage DC		٧	460		
Rated current		Α	16		
Utilization category			gL/gG (cable protection/equipment protection)		
Breaking capacity		kA	80		
Colour code			None		
Type of fuse status indicator			None		
Power loss at rated current		W			
Mounting holes			M6		
Centre-to-centre distance of connections		mm	96.9		