



Fuse-link, low voltage, 50 A, AC 660 V, DC 460 V, BS88, 27 x 129 mm, gL/gG, BS

**TBC50**

Product name	Eaton Bussmann series low voltage British standard fuse	
Part no.	TBC50	
EAN	5027590513173	
Product Length/Depth	129 millimetre	
Product height	27 millimetre	
Product width	27 millimetre	
Product weight	89.9 gram	
Compliances	RoHS Compliant CE Marked	
Certifications	EAC BS88 IEC 60269	
Product Tradename	None	
Product Type	Low voltage British standard fuse	
Product Sub Type	None	
Amperage Rating	50 A	
Voltage rating	660 V	
Voltage type	AC/DC	
Breaking capacity	80 kA	
Class	Class gG/gL	
Application	general industrial applications	
Fuse type	TBC	
Fitted with:	Centre bolted tags	
Connection	111 mm fixing centre	

**Technical data ETIM 8.0**

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		Other
Type of current		AC/DC
Rated voltage AC	V	660
Rated voltage DC	V	460
Rated current	A	50
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	
Mounting holes		M8
Centre-to-centre distance of connections	mm	111