



Fuse-link, LV, 160 A, AC 660 V, DC 350 V, BS88/B2, 34 x 137 mm, gL/gG, BS



TF160

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		TF160
EAN		5027590513739
Product Length/Depth		137 millimetre
Product height		34 millimetre
Product width		34 millimetre
Product weight		200.8 gram
Compliances		Contact Manufacturer
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Amperage Rating		160 A
Voltage rating		660 V
Voltage type		AC/DC
Breaking capacity		80 kA
Class		Class gG/gL
Application		general industrial applications
Fuse type		TF
Fuse size		BS88/B2
Fitted with:		Centre bolted tags
Connection		111 mm fixing centre
Suitable for		RS200 Red spot fuse holder

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		B2
Type of current		AC/DC
Rated voltage AC	V	660
Rated voltage DC	V	350
Rated current	A	160
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	
Mounting holes		M8
Centre-to-centre distance of connections	mm	111