



Fuse-link, low voltage, 200 A, AC 1500 V, DC 660 V, 40 x 192 mm, gL/gG, BS



Powering Business Worldwide™

TFC200

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		TFC200
EAN		5996516026403
Product Length/Depth		48 millimetre
Product height		47 millimetre
Product width		215 millimetre
Product weight		498 gram
Compliances		Not Applicable
Certifications		BS
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Amperage Rating		200 A
Voltage rating		1500 V
Voltage type		AC/DC
Breaking capacity		63 kA
Class		Class gG/gL
Fuse type		TFC
Connection		Bolt-on

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		Other
Type of current		AC/DC
Rated voltage AC	V	1,500
Rated voltage DC	V	660
Rated current	A	200
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	63
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	
Mounting holes		M10
Centre-to-centre distance of connections	mm	168.4