



Fuse-link, LV, 315 A, AC 660 V, DC 460 V, BS88/B3, 53 x 137 mm, gL/gG, BS



TKF315

| | | |
|----------------------|--|---|
| Product name | | Eaton Bussmann series low voltage British standard fuse |
| Part no. | | TKF315 |
| EAN | | 5996516026465 |
| Product Length/Depth | | 137 millimetre |
| Product height | | 53 millimetre |
| Product width | | 53 millimetre |
| Product weight | | 488 gram |
| Compliances | | CE Marked RoHS Compliant |
| Certifications | | IEC 60269 KEMA BS88 EAC |
| Product Tradename | | None |
| Product Type | | Low voltage British standard fuse |
| Product Sub Type | | None |
| Amperage Rating | | 315 A |
| Voltage rating | | 660 V |
| Voltage type | | AC/DC |
| Breaking capacity | | 80 kA |
| Class | | Class gG/gL |
| Application | | general industrial applications |
| Fuse type | | TKF |
| Fuse size | | BS88/B3 |
| Fitted with: | | Centre bolted tags |
| Connection | | 111 mm fixing centre |

Technical data ETIM 8.0

| | | |
|--|----|---|
| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556) | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011]) | | |
| Fuse construction type according to IEC 60269 | | Other |
| Type of current | | AC/DC |
| Rated voltage AC | V | 660 |
| Rated voltage DC | V | 460 |
| Rated current | A | 315 |
| Utilization category | | gL/gG (cable protection/equipment protection) |
| Breaking capacity | kA | 80 |
| Colour code | | None |
| Type of fuse status indicator | | None |
| Power loss at rated current | W | |
| Mounting holes | | M8 |
| Centre-to-centre distance of connections | mm | 111 |