



Fuse-link, low voltage, 750 A, AC 660 V, DC 350 V, BS88/C3, 83 x 210 mm, gL/gG, BS

TLM750

Product name	Eaton Bussmann series low voltage British standard fuse
Part no.	TLM750
EAN	5996516026533
Product Length/Depth	210 millimetre
Product height	83 millimetre
Product width	83 millimetre
Product weight	0.015 gram
Compliances	CE Marked RoHS Compliant
Certifications	EAC BS88 IEC 60269
Product Tradename	None
Product Type	Low voltage British standard fuse
Product Sub Type	None
Amperage Rating	750 A
Voltage rating	660 V
Voltage type	AC/DC
Breaking capacity	80 kA
Class	Class gG/gL
Application	general industrial applications
Fuse type	TLM
Fuse size	BS88/C3
Fitted with:	Centre bolted tags
Connection	133/184 mm fixing centre

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)	
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])	
Fuse construction type according to IEC 60269	C3
Type of current	AC/DC
Rated voltage AC	V 660
Rated voltage DC	V 350
Rated current	A 750
Utilization category	gL/gG (cable protection/equipment protection)
Breaking capacity	kA 80
Colour code	None
Type of fuse status indicator	None
Power loss at rated current	W
Mounting holes	M10
Centre-to-centre distance of connections	mm 183.8