

## XS10

|                      |  |   |
|----------------------|--|---|
| Product name         |  | Eaton Bussmann series low voltage British standard fuse |
| Part no.             |  | XS10  |
| EAN                  |  | 5027590515269   |
| Product Length/Depth |  | 79 millimetre   |
| Product height       |  | 27 millimetre   |
| Product width        |  | 27 millimetre   |
| Product weight       |  | 66.4 gram   |
| Compliances          |  | CE  |
| Product Tradename    |  | None  |
| Product Type         |  | Low voltage British standard fuse                       |
| Product Sub Type     |  | None  |
| Amperage Rating      |  | 10 A  |
| Voltage rating       |  | 440 V   |
| Breaking capacity    |  | 80 kA   |
| Class                |  | Class gG/gL   |
| Application          |  | general industrial applications                         |
| Fuse type            |  | XS  |
| Fitted with:         |  | Offset bladed tags                                      |
| Connection           |  | Blade end   |
| Suitable for         |  | SC125 Safeclip fuse holder                              |

## Technical data ETIM 8.0

|  |    |   |
|--|----|---|
| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)  |    |   |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011]) |    |   |
| Fuse construction type according to IEC 60269  |    | F3  |
| Type of current  |    | AC  |
| Rated voltage AC   | V  | 440   |
| Rated voltage DC   | V  |   |
| Rated current  | A  | 10  |
| Utilization category   |    | gL/gG (cable protection/equipment protection) |
| Breaking capacity  | kA | 80  |
| Colour code  |    | None  |
| Type of fuse status indicator  |    | None  |
| Power loss at rated current  | W  |   |
| Mounting holes   |    |   |
| Centre-to-centre distance of connections   | mm |   |