



**Eaton ATS rack PDU, 1U, Inputs (2) C20, 3.84 kW max, 16A, 200-240V, Outlets 8XC13:1XC19**



**Catalog No. EATS16**

**Delivery program**

Type		ATS
Electrical Connection		Connecting cord with plug
Evaluation		Local
Mounting Dimension (metrical)		43
Mounting Dimension (standardised)		482.6 mm (19 inch)
Ampere Meter		Yes
Switchable		No
Over Voltage Category		2
Input Connection		(2) C20
Cord Length		2m
Wattage		3.84 kW max
Input Voltage		200-240V
Phase		Single-phase
Frequency Rating		50/60 Hz
With Temperature Measurement		No
Communication		No
SNMP		No
Ethernet Interface		No
Display		Yes
LED Indicator		Yes
Serial Interface		No
Mass Configuration		No
Form Factor		1U
Outlet Control		No
Package Contents		ATS Quick start guide Safety manual 2 x Input cables: C19-C20 (1.80m) 2 x Input cable lockers Plastic strips for output locking RS232 cable Accessories for rack installation
With Mounting Material		Yes
Operating Temperature		0° to 40°C (32° to 104°F)
Outlets		8XC13:1XC19
Number of Outputs C13		8
Number of Outputs C19		1
Number of Outputs C20		2
Number of Outputs Hardwired		0
Num of Outputs PC (SCHUKO)		0
Number of Outputs (Other)		0
Number of Outlets with Earth Pin		9
With Fuse		No

Mains Filter		No
Amperage Rating		16A
Mounting Direction		Horizontal
Color		Black
ETIM Class		EC002762

## Technical data ETIM 7.0

Domestic switching devices (EG000013) / Power distribution unit (PDU) (EC002762)		
Electric engineering, automation, process control engineering / Electrical installation, device / Low-voltage distribution system (mobile) / Low-voltage distribution systems (mobile, unspecified) (ecl@ss10.0.1-27-14-26-90 [AKN612013])		
Mounting dimension (standardised)		482.6 mm (19 inch)
Mounting dimension	mm	43
Mounting direction		Horizontal
Electrical connection		Connecting cord with plug
Type of electric connection		Other
Cable length	m	
Number of socket outlets with protective contact		0
Number of socket outlets with earth pin		9
Number of C13 socket outlets		8
Number of C19 socket outlets		1
Number of C20 socket outlets		2
Number of UK BS1363 sockets		
number of socket outlets swiss standard type 13		
number of socket outlets swiss standard type 15		
number of socket outlets swiss standard type 23		
number of socket outlets swiss standard type 25		
Number of other socket outlets		0
Number of height units		
Length	mm	430
Width	mm	250
Height	mm	43
Depth	mm	430
Supply voltage	V	
Over voltage category		2
Mains filter		No
Switchable		No
SNMP		No
With display		Yes
Evaluation		Local
With LED indication		Yes
With fuse		No
Ampere meter		Yes
With temperature measurement		No
With mounting material		Yes