



Eaton ATS Rack PDU, 1U, entrées (2) C20, 3,84 kW max., 16 A, 200-240 V,
Prises 8XC13:1XC19



N° de catalogue EATS16

Gamme de livraison

Type	ATS
Electrical Connection	Cordon et prise de connexion
Evaluation	Local
Mounting Dimension (metrical)	43
Mounting Dimension (standardised)	482,6 mm (19 pouces)
Ampere Meter	Oui
Switchable	Non
Over Voltage Category	2
Input Connection	(2) C20
Cord Length	2 m
Wattage	3,84 kW max
Input Voltage	200-240V
Phase	Monophasé
Frequency Rating	50/60 Hz
With Temperature Measurement	Non
Communication par bus de terrain	No
SNMP	Non
Ethernet Interface	Non
Display	Oui
LED Indicator	Oui
Serial Interface	Non
Mass Configuration	Non
Form Factor	1U
Outlet Control	Non
Package Contents	ATS Guide de démarrage rapide Manuel de sécurité 2 câbles d'entrée : C19-C20 (1,80 m) 2 systèmes de rétention pour câble d'entrée Bandes en plastique pour le verrouillage de la sortie Câble RS232 Équipements complémentaires pour montage en rack
With Mounting Material	Oui
Operating Temperature	0 à 40 °C (32 à 104 °F)
Outlets	8XC13:1XC19
Number of Outputs C13	8
Number of Outputs C19	1
Number of Outputs C20	2
Nombre de sorties câblées	0
Num of Outputs PC (SCHUKO)	0
Number of Outputs (Other)	0
Number of Outlets with Earth Pin	9
With Fuse	Non

Mains Filter		Non
Amperage Rating		16A
Mounting Direction		Horizontal
Color		Noir

Caractéristiques techniques ETIM 7.0

Appareillage terminal, prises et commandes (résidentiel) (EG000013) / Unité de distribution d'énergie (PDU) (EC002762)		
Electricité, Electronique, Automatisation et Commande / Installation électrique, appareillage / Distributeur à basse tension mobile / Distributeur à basse tension mobile (non classé) (ecl@ss10.0.1-27-14-26-90 [AKN612013])		
Mounting dimension (standardised)		482.6 mm (19 inch)
Mounting dimension	mm	43
Mounting direction		Horizontal
Electrical connection		Connecting cord with plug
Type of electric connection		Other
Cable length	m	
Number of socket outlets with protective contact		0
Number of socket outlets with earth pin		9
Number of C13 socket outlets		8
Number of C19 socket outlets		1
Number of C20 socket outlets		2
Number of UK BS1363 sockets		
number of socket outlets swiss standard type 13		
number of socket outlets swiss standard type 15		
number of socket outlets swiss standard type 23		
number of socket outlets swiss standard type 25		
Number of other socket outlets		0
Number of height units		
Length	mm	430
Width	mm	250
Height	mm	43
Depth	mm	430
Supply voltage	V	
Over voltage category		2
Mains filter		No
Switchable		No
SNMP		No
With display		Yes
Evaluation		Local
With LED indication		Yes
With fuse		No
Ampere meter		Yes
With temperature measurement		No
With mounting material		Yes