

Carrier, +label, START

Part no. Q25TS-111  
046192

| <b>General specifications</b>  |  |
|--|--|
| Product name   | Eaton Moeller® series RMQ16 Accessory Label mount with insert label                            |
| Part no.   | Q25TS-111  |
| EAN  | 4015080461920  |
| Product Length/Depth   | 1 millimetre   |
| Product height   | 38 millimetre  |
| Product width  | 25 millimetre  |
| Product weight   | 0.009 kilogram   |
| Certifications   | UL/CSA certification not required  |
| Product Tradename  | RMQ16  |
| Product Type   | Accessory  |
| Product Sub Type   | Label mount with insert label  |
| <b>Features &amp; Functions</b>  |  |
| Color  | Black  |
| Inscription  | START  |
| Language   | English  |
| Shape  | Rectangular  |
| <b>Climatic environmental conditions</b>   |  |
| Ambient operating temperature - min  | -25 °C   |
| Ambient operating temperature - max  | 60 °C  |
| <b>Communication</b>   |  |
| Connection to SmartWire-DT   | No   |
| <b>Design verification</b>   |  |
| Equipment heat dissipation, current-dependent Pvid                               | 0 W  |
| Heat dissipation capacity Pdis   | 0 W  |
| Heat dissipation per pole, current-dependent Pvid                                | 0 W  |
| Rated operational current for specified heat dissipation (In)                    | 0 A  |
| Static heat dissipation, non-current-dependent Pvs                               | 0 W  |
| 10.2.2 Corrosion resistance  | Meets the product standard's requirements.   |
| 10.2.3.1 Verification of thermal stability of enclosures                         | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat       | Meets the product standard's requirements.   |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                 | Please enquire   |
| 10.2.5 Lifting   | Does not apply, since the entire switchgear needs to be evaluated.                             |
| 10.2.6 Mechanical impact   | Does not apply, since the entire switchgear needs to be evaluated.                             |
| 10.2.7 Inscriptions  | Meets the product standard's requirements.   |
| 10.3 Degree of protection of assemblies  | Does not apply, since the entire switchgear needs to be evaluated.                             |
| 10.4 Clearances and creepage distances   | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock   | Does not apply, since the entire switchgear needs to be evaluated.                             |
| 10.6 Incorporation of switching devices and components                           | Does not apply, since the entire switchgear needs to be evaluated.                             |
| 10.7 Internal electrical circuits and connections                                | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   | Is the panel builder's responsibility.   |
| 10.9.2 Power-frequency electric strength   | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage   | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material                         | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   | Not applicable.  |
| 10.11 Short-circuit rating   | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |

|                                     |  |  |  |
|-------------------------------------|--|--|--|
| 10.12 Electromagnetic compatibility |  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.           |
| 10.13 Mechanical function           |  |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

## Technical data ETIM 9.0

|  |  |    |             |
|--|--|----|-------------|
| Low-voltage industrial components (EG000017) / Text plate for command devices (EC000624)   |  |    |             |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Identification plate for command devices (ecl@ss13-27-37-12-25 [AKF043019]) |  |    |             |
| Literal imprint  |  |    | Start       |
| Language of the imprint  |  |    | English     |
| Imprint ISO symbols  |  |    | None        |
| Colour   |  |    | Black       |
| Shape  |  |    | Rectangular |
| Width  |  | mm | 25          |
| Height   |  | mm | 38          |
| Outer diameter   |  | mm | 0           |