

**Short-circuit protective breaker, Iu 1.6 A, Irm 24.8 A, Screw terminals,
Also suitable for motors with efficiency class IE3.**

**Part no. PKM0-1,6
072725**

General specifications		
Product name		Eaton Moeller® series PKM0 Short-circuit protective breaker
Part no.		PKM0-1,6
EAN		4015080727255
Product Length/Depth		76 millimetre
Product height		93 millimetre
Product width		45 millimetre
Product weight		0.288 kilogram
Certifications		IEC/EN 60947 VDE 0660
Product Tradename		PKM0
Product Type		Short-circuit protective breaker
Product Sub Type		None
Catalog Notes		An appropriate overload relay must be fitted to protect motors against overload. IE3-ready devices are identified by the logo on their packaging. Refer to catalog CA034001DE for the allocation of short circuit protection and contactor
Features & Functions		
Actuator type		Turn button
Number of poles		Three-pole
General information		
Connection		Screw terminals
Degree of protection		IP20 Terminals: IP00
Lifespan, electrical		100,000 operations
Lifespan, mechanical		100,000 Operations
Mounting position		Can be snapped on to IEC/EN 60715 top-hat rail with 7.5 or 15 mm height.
Operating frequency		40 Operations/h
Overvoltage category		III
Pollution degree		3
Product category		Motor protective circuit breaker
Protection		Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
Rated impulse withstand voltage (Uimp)		6000 V AC
Shock resistance		25 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
Suitable for		Also motors with efficiency class IE3
Temperature compensation		≤ 0.25 %/K, residual error for T > 40° -5 - 40 °C to IEC/EN 60947, VDE 0660 -25 - 55 °C, Operating range
Type		Short-circuit protective device only
Climatic environmental conditions		
Altitude		Max. 2000 m
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		55 °C
Ambient operating temperature (enclosed) - min		25 °C
Ambient operating temperature (enclosed) - max		40 °C
Ambient storage temperature - min		40 °C
Ambient storage temperature - max		80 °C
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Terminal capacities		

Terminal capacity (flexible with ferrule)			1 x (1 - 6) mm ² , ferrule to DIN 46228 2 x (1 - 6) mm ² , ferrule to DIN 46228
Terminal capacity (solid)			2 x (1 - 6) mm ² 1 x (1 - 6) mm ²
Terminal capacity (solid/stranded AWG)			18 - 10
Stripping length (main cable)			10 mm
Tightening torque			1 Nm, Screw terminals, Control circuit cables 1.7 Nm, Screw terminals, Main cable
Electrical rating			
Rated frequency - min			50 Hz
Rated frequency - max			60 Hz
Rated operational current (Ie)			1.6 A
Rated operational power at AC-3, 220/230 V, 50 Hz			0.25 kW
Rated operational power at AC-3, 380/400 V, 50 Hz			0.37 kW
Rated operational power at AC-3, 440 V, 50 Hz			0.55 kW
Rated operational power at AC-3, 500 V, 50 Hz			0.75 kW
Rated operational power at AC-3, 690 V, 50 Hz			1.1 kW
Rated operational voltage (Ue) - min			690 V
Rated operational voltage (Ue) - max			690 V
Rated uninterrupted current (Iu)			1.6 A
Short-circuit rating			
Rated short-circuit breaking capacity Icu at 400 V AC			150 kA
Short-circuit release			24.8 A, I _{rm} , Setting range max. ± 20% tolerance, Trip blocks Basic device fixed 15.5 x I _u , Trip Blocks
Switching capacity			
Switching capacity			1.6 A, AC-3 up to 690 V 1.6 A (3 contacts in series), DC-5 up to 250V
Trip blocks			
Overload release current setting - min			0 A
Overload release current setting - max			0 A
Design verification			
Equipment heat dissipation, current-dependent P _{vid}			5.36 W
Heat dissipation capacity P _{diss}			0 W
Heat dissipation per pole, current-dependent P _{vid}			1.79 W
Rated operational current for specified heat dissipation (I _n)			1.6 A
Static heat dissipation, non-current-dependent P _{vs}			0 W
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Motor protection circuit-breaker (EC000074)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Motor protection circuit-breaker (ecl@ss13-27-37-04-01 [AGZ529021])		
Overload release current setting	A	0 - 0
Adjustment range undelayed short-circuit release	A	25 - 25
With thermal overload protection		No
Phase failure sensitive		No
Switch off technique		Magnetic
Rated operating voltage	V	690 - 690
Rated permanent current Iu	A	1.6
Rated operation power at AC-3, 230 V	kW	0.25
Rated operation power at AC-3, 400 V	kW	0.37
Power loss	W	5.36
Type of electrical connection of main circuit		Screw connection
Type of control element		Turn button
Device construction		Built-in device fixed built-in technique
With integrated auxiliary switch		No
With integrated under voltage release		No
Number of poles		3
Rated short-circuit breaking capacity Icu at 400 V, AC	kA	150
Degree of protection (IP)		IP20
Height	mm	93
Width	mm	45
Depth	mm	76