

Pressure switch, 2W gold-plated, 7bar

Part no. MCS4-SOND910-G
087792



General specifications		
Product name		Eaton Moeller® series MCS Pressure switch
Part no.		MCS4-SOND910-G
EAN		4015080877929
Product Length/Depth		111 millimetre
Product height		66 millimetre
Product width		96 millimetre
Product weight		0.383 kilogram
Certifications		IEC/EN 60947-5-1 CSA File No.: 012528 CSA Class No.: 3211-06 CSA CSA-CC22.2 No. 14
Product Tradename		MCS
Product Type		Pressure switch
Product Sub Type		None
Catalog Notes		Note on use: This product complies with Low-Voltage Directive 2014/35/EC and EMC Directive 2014/30/EC and meets the requirements in EN 60947-5-1. This product does not meet the rail industry's standard requirements. Accordingly, the user must review it separately for the specific application at hand.
Features & Functions		
Electric connection type		Screw connection
Features		Variable switching differential
General information		
Actuator diameter		0 mm
Bursting pressure		90 bar
Connection		Inner thread gas cylindrical (BSPP)
Connection type		Tunnel terminal
Degree of protection		IP65 NEMA Other
Lifespan, electrical		1,000,000 Operations
Operating frequency		1500 Operations/h
Operating pressure - max		7000 hPa
Overvoltage category		III
Pollution degree		3
Product category		Pressure switches
Rated impulse withstand voltage (Uimp)		1500 V AC
Suitable as		2-point controller Guard
Test pressure		32 bar
Ambient conditions, mechanical		
Mounting position		Vertical and 90° in all directions
Shock resistance		10 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms
Vibration resistance		36 Hz, Amplitude 1 mm, (IEC/EN 60068-2-6)
Climatic environmental conditions		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Environmental conditions		Compliant to 2014/35/EC, 2014/30/EC and EN 60947-5-1. Accordingly, the user must review it separately for the specific application at hand.
Terminal capacities		

Terminal capacity (flexible with ferrule)			1 x (0.5 - 1.5) mm ² , ferrules to DIN 46228
Terminal capacity (solid)			1 x (0.75 - 2.5) mm ² 2 x (0.75 - 1.5) mm ²
Screw size			M2.6, Terminal screw
Tightening torque			0.4 Nm, Screw terminals
Electrical rating			
Rated frequency - max			50 Hz
Rated insulation voltage (Ui)			125 V
Rated operational current (Ie)			2 A at AC-15, 230 V, 50/60Hz 0.25 A at DC-13, 110 V 1 A at DC-13, 24 V
Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V			0 A
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V			0 A
Rated operational power at AC-3, 380/400 V, 50 Hz			0 kW
Rated operational voltage (Ue) at AC - min			0 V
Rated operational voltage (Ue) at AC - max			0 V
Rated operational voltage (Ue) at DC - min			0 V
Rated operational voltage (Ue) at DC - max			110 V
Short-circuit rating			
Short-circuit protection rating			Max. 2 A gG/gL, Fuse, Contacts
Contacts			
Number of auxiliary contacts (change-over contacts)			2
Number of auxiliary contacts (normally closed contacts)			0
Number of auxiliary contacts (normally open contacts)			0

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Pressure switch (EC000243)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Monitoring equipment (low-voltage switch technology) / Pressure monitoring equipment (ecI@ss13-27-37-18-14 [AKF108019])			
Suitable as guard			Yes
Suitable as 2-point controller			Yes
Suitable as limiter			No
Max. operating pressure		hPa	7000
Engaging pressure		bar	0 - 4.2
Initial setting		hPa	0 - 0
Switch off pressure		bar	0 - 4.5
End setting		hPa	0 - 0
Pressure-switching differential		bar	0
Max. test pressure		bar	32
Bursting pressure		bar	90
Medium temperature		°C	25 - 80
Connection			Internal thread cylindrical BSPP-G (ISO 228-1)
Thread size			1/2 inch
Rated voltage Ue at AC 50 Hz		V	0 - 0
Rated voltage Ue at AC 60 Hz		V	0 - 0
Rated voltage Ue at DC		V	0 - 110
Initial value measuring range pressure		Pa	0
End value measuring range pressure		Pa	0
Rated operation power at AC-3, 400 V		kW	0
Switching capacity at AC-3, 240 V		kA	0
Rated operation current Ie at AC-1, 400 V		A	0
Rated operation current Ie at AC-3, 400 V		A	0
Number of auxiliary contacts as normally open contact			0
Number of auxiliary contacts as normally closed contact			0
Number of auxiliary contacts as change-over contact			2
Type of electric connection			Screw connection

Number of normally closed contacts as main contact		0
Number of normally open contacts as main contact		0
Adjustable current range	A	0 - 0
With hand operation		No
With manual on/off switch		No
Electronic version		No
With display		No
Explosion-proof		No
Degree of protection (IP)		IP65
Degree of protection (NEMA)		Other
Height	mm	66
Width	mm	96
Diameter	mm	0
Depth	mm	111