

Indicator light, flush, white



Part no. Q18LF-WS  
088406  
EL Number 4356303  
(Norway)

General specifications		
Product name		Eaton Moeller® series RMQ16 Indicator light
Part no.		Q18LF-WS
EAN		4015080884064
Product Length/Depth		59 millimetre
Product height		18 millimetre
Product width		18 millimetre
Product weight		0.009 kilogram
Certifications		CSA File No.: 46552 CSA IEC/EN 60947 CSA Class No.: 3211-03 UL File No.: E29184 CE CSA-C22.2 No. 14-05 UL 508 UL UL Category Control No.: NKCR IEC/EN 60947-5
Product Tradename		RMQ16
Product Type		Indicator light
Product Sub Type		None
Catalog Notes		Use of insulated ferrule ISH 2,8 > 24 V AC/DC recommended Use of insulated ferrule ISH 2,8 > 50 V AC or 120 V DC is mandatory, even on unused blade terminals Without light elements
Features & Functions		
Bezel color		Black
Bezel material		Plastic
Design		Flat
Fitted with:		LED W2x4, 6d, max. 30 V, 1 W Front ring
Lens color		White
General information		
Degree of protection		NEMA 1
Degree of protection (front side)		IP65
Opening diameter		16 mm
Overvoltage category		III
Pollution degree		3
Product category		RMQ16
Size		Front dimensions: 18 x 18 mm
Rated impulse withstand voltage (Uimp)		800 V AC
Terminal capacity		0.5 - 1.0 mm²
Terminal size		2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors 2.8 x 0.8 mm to DIN 46244, Blade terminal
Type		Indicator lights
Ambient conditions, mechanical		
Mounting position		As required
Shock resistance		40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
Climatic environmental conditions		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		60 °C
Ambient operating temperature (enclosed) - min		25 °C

Ambient operating temperature (enclosed) - max			40 °C
Climatic proofing			Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
<b>Electrical rating</b>			
Rated insulation voltage (Ui)			250 V
Rated operational voltage (Ue) at AC - max			24 V
<b>Communication</b>			
Connection to SmartWire-DT			No
<b>Design verification</b>			
Equipment heat dissipation, current-dependent Pvid			0 W
Heat dissipation capacity Pdis			0 W
Heat dissipation per pole, current-dependent Pvid			0 W
Rated operational current for specified heat dissipation (In)			0 A
Static heat dissipation, non-current-dependent Pvs			0 W
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Please enquire
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			Not applicable.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Front element for indicator light (EC000223)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for warning lights (ecl@ss13-27-37-12-11 [AKF029019])			
Suitable for number of built-in signal lights			1
Colour lens			White
Construction type lens			Square
Hole diameter		mm	16
Width opening		mm	0
Height opening		mm	16
With front ring			Yes
Material front ring			Plastic
Colour front ring			Black
Type of lens			Flat
Degree of protection (IP), front side			IP65
Degree of protection (NEMA)			1